

WCS, WC COMBI-PACK, TOILETS, 1PC-SIPHONIC, FLOOR-MOUNTED TOILETS SUBWAY

PRODUCT INFORMATION

1 . POSITION



Model	6616US
Width	15" inch
Depth	29 3/8" inch
Weight	119,05 lbs
Description	<p>Overall dimensions: (L) 28 3/8" x (W) 15" x (H) 28 3/4" Sanitary porcelain composed of: Consisting of: Siphonic WC, rough in 12" from the wall, Tank, bottom inlet, flushing mechanism with chrome trip lever, dual flush 1.6/1.0 gpf, WC-seat and cover with QuickRelease and SoftClosing hinges 9M30 U1 01, incl. fastening set This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/8" (730mm) x 15" (380") x 28 3/4" (730mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 6616US. Certifications: IAPMO(cUPC), City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14 siphonic jet model concealed trapway elongated bowl one year limited warranty min Water pressure: 8 psi water surface: 5 1/2" x 6 3/4" (140 x 170 mm) trap diameter: 2 1/8" (51mm) trap seal: 2 1/4" (55mm) minimum rough-in: 12" (305 mm) rough-in bottom outlet duo-push button chrome finish</p>
Water use	1,28 / 0 gal
Installation	floor-standing
Outlet	concealed trapway
Material	Sanitary porcelain
Lead	4

Specification texts

; One-piece toilet; Overall dimensions: (L) 28 3/8" x (W) 15" x (H) 28 3/4"; Sanitary porcelain; Size: 15" x 29 3/8" (380 x 745 mm); Oval; floor-standing; Water use: 1,28 / 0 gal; Leed: 4; concealed trapway; This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/8" (730mm) x 15" (380") x 28 3/4" (730mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 6616US.; Certifications: IAPMO(cUPC), City of Los Angeles and others, Code Compliance: UPC, IPC, NSPC, NPC Canada and others, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; min Water pressure: 8 psi; water surface: 5 1/2" x 6 3/4" (140 x 170 mm); trap diameter: 2 1/8" (51mm); trap seal: 2 1/4" (55mm); minimum rough-in: 12" (305 mm) rough-in; duo-push button chrome finish; bottom outlet

COLOURS

White Alpin 6616US01 4051202086251

TECHNICAL DRAWINGS

6616US

